HP DesignJet XT950 36-in Multifunction Printer



The world's most efficient half size to D size printing experience to boost productivity¹



*Product image may differ from actual product

MOST EFFICIENT¹-Save time, get through more

- Pick up your jobs quickly and simply-stacker holds up to 40 pages flat for easy collection.²
- Do it all-seamlessly print your half-size jobs with integrated input and output trays, keeping pages sorted by size.
- Move projects forward with fast print speeds, 300-ft roll, and high image quality with pigmentbased HP Flex Tech Inks.
- Simplify scan and copy workflows with personalized one-click shortcuts from the front panel.

CONNECTED-Secure and seamless collaboration

- Save time with HP Click-print in fewer steps and avoid printing errors with print preview.
- Protect your printer and data from cyberthreats without any effort thanks to HP Wolf Pro
- Stay on task with HP app³-manage your device and print from virtually anywhere using your mobile or tablet.
- Share drawings and collaborate with colleagues wherever they are with the easy-to-use frontloading scanner.

GO BEYOND-Meet office and environmental

- Advance environmental goals-printer is made with at least 35% recycled plastics⁴ and supplies can be recycled⁵.
- Invest in a robust and compact plotter that's designed to last.
- Reduce energy and ink waste-auto schedule printer on/off usage and enjoy efficient ink maintenance routines.

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Messaging Footnotes

³ Requires HP app download available at https://www.hp.com/go/mobileprinting. Certain features are available in English language only and may vary by printer model/country, and between desktop/mobile applications. HP reserves the right to introduce charges for use of functionality facilitated by the HP app. Internet access required and may not be available in all countries. HP account required for full functionality. List of supported operating systems available in app stores.

⁴ Declared %RCP content is based on the quantity and weight of parts made with RCP resin over the total plastic parts.
⁵ Program availability varies. See https://www.hp.com/go/recycle













¹ The HP Design Jet 1950 is faster than its main competitors: 44% faster than competitor A and 43% faster than competitor B in end-to-end performance, including job preparation with printing software, processing, printing, and collection, Testing performed by Sogeti, April 2023. Detailed test report is available upon request.

Based on test results using D size, plain paper, and standard configuration. Stacking capacity is subject to paper type, printed file and ambient conditions.

Technical specifications

Print	
Speed	Up to 1.5 in/sec (color, 200 dpi), up to 4.5 in/sec (grayscale, 200 dpi)
Print speed	21 sec/page for D size, 120 D size 24" x 36" prints per hour 1
Print resolution	Up to 2400 x 1200 optimized dpi
Technology	HP Thermal Inkjet
Margins	Roll: 0.2 x 0.2 x 0.2 in
	Sheet: 0.2 x 0.2 x 0.2 x 0.2 in
Ink types	Pigment-based (C, M, Y, mK)
Ink cartridges	4 (C, M, Y, mK)
Cartridge size	300 ml, 130 ml
Ink drop	6 pl (C, M, Y); 12.6 pl (mK)
Printheads	1 (C, M, Y, mK)
Printhead nozzles	1376 per color; 5504 in total
Line accuracy	±0.1% ²
Minimum line width	0.0008 in (via raster driver)
Max optical density	15 L* min/1.7 D ³
Print modes	21 sec/page for D size, 120 D size 24" x 36" prints per hour ¹
Scan and copy	
Scan speed	Up to 1.5 in/sec (color, 200 dpi), up to 4.5 in/sec (grayscale, 200 dpi);
Scan resolution	Up to 600 dpi
Scan format	JPEG, PDF, TIFF
Scan destinations	Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP app.
Maximum scan width	36 x 109 in
Scan width	36 x 109 in
Maximum scan length	23 ft ⁴
Technology	Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method
Thickness	Up to 0.03 in
Media	
Applications	Line drawings; Renderings; Presentations; Maps; Posters
Handling	Sheet feed, roll feed, front-loading input tray (100 sheet capacity for 11" X 17"; 50 sheet capacity for 12"X 18"), sheet organizer (50 sheet capacity ⁵), stacker (40 sheet capacity ⁵), automatic horizontal cutter
Maximum media width	capacity"), stacker (40 sneet capacity"), automatic norizontal cutter 36 in
Media rolls	30 in
Roll size	14.5 to 36 in
Maximum roll weight	14.5 to 36 in 28.6 lb
Maximum roll diameter	5.5 in
Sheet/board size	5.5 in Front-loading input tray: 8.3 x 11 to 12 x 18 in; Manual feed: 8.3 x 11 to
	36 x 66 in
Standard sheets/boards	Input tray: A, B; Manual feed: A, B, C, D, E
Media types	Bond and coated paper (bond, coated, heavyweight coated, plain, bright white, blueprint), technical paper (natural tracing), film (clear, matte), photographic paper (ID satin, ID gloss), self-adhesive (adhesive matte/gloss, adhesive polypropylene gloss), Polypropylene (matte)
Embedded controller	
Memory	2 GB
Hard disk	None

Windows and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Remote print enabled Yes One-click multi-size printing Yes Drivers Raster driver for macOS and Windows, HP Click Driver for Windows 11, HP-Cl_I/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 8021x compatibility, TLS/SSI Semi-permanent-queue Erase, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 554 x 28.3 x 38.1 in Shipping 62 x 24.8 x 30.7 in Welght Printer 156.5 ib Shipping 213.8 ib Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and IOS Environmental ranges Operating temperature 41 to 104°F Operating altitude Up to 9843 ft Storage temperature 35 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 58 B(A) (operating), <16 dB(A) (idle) Sound power Printing: 58 B(A) (operating), <3.4 B(A) (idle) Fower Consumption 35 W (printing). <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Pmox (RSM), India (BIS) Safety USA and Canada (CSA certified); EU (RED Directive, EN 623681 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (RSM), India (BIS) Electromagnetic Environmental ENERCY STAR, EPEAT, UL ECOLOGO* certified inks, CE marking (Including WEEE, RoHS, REACH, ErP), in compliance with applicable WW RoHS materials restriction requirements.	Job storage	2.7 GB reprint queue
Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n	Native print languages	TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4
Printing paths Wi-Fi Direct, remote printing, HP Click App, HP Click Driver for Windows 11, Apple AirPrint and HP app for Android and 10'S devices, Windows and macco'S printer drivers, printing support for Chrome OS, print from USB pen drive Remote print enabled Yes One-click multi-size printing Yes Drivers Roster driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows 11, HP-GL/2 driver for Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, Semi-permanent-queue Frase, NTLI, W2, HP Web Jet Admin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 55.4 x 28.3 x 38.1 in Shipping 62 x 24.8 x 30.7 in Weight Printer 156.5 ib Shipping 213.8 lb Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating temperature 41 to 104°F Recycled plastic in printer 36% Acoustics Sound power Printing: 42 dB(A) (operating), <3.6 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.8 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Autoscheduled printer on/off usage, compliant; Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRSM), India (IES), EU (IRED Directive, EN 623681 compliant; Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRSM), India (IES), EU (IRED Directive, Australia (ACMA), New Zealand (IRSM), China (ICSC), Japan (VCCI); Morea (IRCC) Environmental Environmental Environmental Electromagnetic Compliant with Class B requirements, including: U	Connectivity	
Windows 11, Apple AirPrint Tand HP app for Android and IOS devices, Windows and maco Sp printer drivers, printing support for Chrome OS, print from USB pen drive Remote print enabled One-click multi-size printing Ves Drivers Rester driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMP-v3, 8021x compatibility, TLS/SSI Semi-permanent-queue Erase, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 55.4 x 28.3 x 38.1 in Shipping 62 x 24.8 x 30.7 in Weight Printer 156.5 ib Shipping 213.8 lb Included What's in the box HP DesignJet X1950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating latitude Up to 9843 ft Storage temperature 41 to 104°F Operating altitude Up to 9843 ft Storage temperature 35 to 131°F Recycled plastic in printer Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <16 dB(A) (idle) Power Consumption 35 W (printing). <11 W (ready), <3.5 W (sleep), <0.1 W (standby), Auto-scheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Amox (ICSA), India (BiS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICSB), EU (RED Directive), Australia (ACMA), New Zealand (RSM), India (BiS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICSB), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCC); Korea (RCC) Environmental Envi	Interfaces	Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n
Drivers Raster driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows, Semi-permanent-queue Errose, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration	Printing paths	Windows 11, Apple AirPrint and HP app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome
Raster driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows 11, HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSI Semi-permanent-queue Errase, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration	Remote print enabled	Yes
11, HP-GL/2 driver for Windows Security features HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SMMPv3, 8021x compatibility, TLS/SSI Semi-permanent-queue Erase, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 55.4 x 28.3 x 38.1 in Shipping 62 x 24.8 x 30.7 in Weight Printer 156.5 lb Shipping 213.8 lb Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating lumidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature 41 to 131°F Recycled plastic in printer Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Pmax Certification Safety USA and Canada (CSA certified): EU (RED Directive, EN 82368-1 compliant): Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (RSM), China (CCC); Jepan (VCC); Korea (RCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHs, REACH, ErP), in compliance with applicable WW RoHs materials restriction requirements.	One-click multi-size printing	Yes
network ports and protocols, SNMPv3, 8021x compatibility, TLS/SSI Semi-permanent-queue Erase, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration Dimensions (W x D x H) Printer 55.4 x 28.3 x 38.1 in Shipping 62 x 24.8 x 30.7 in Weight Printer 156.5 lb Shipping 213.8 lb Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound power Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Amox Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (RSM), India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive, EN 62368-1 compliant, Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (RSM), China (CCC), Japan (VCC); Korea (KCC) Environmental One-year limited hardware warranty. Warranty and support options	Drivers	Raster driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows
Printer 55.4 x 28.3 x 38.1 in Shipping 62 x 24.8 x 30.7 in Weight Printer 156.5 lb Shipping 213.8 lb Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature 43 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Printing: (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive, Australia (ACMA), New Zealand (RSM), China (CCC), Japan (WCC); Karea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO° certified inks, CE marking (including WEE, RoHS, REACH, EPP, In compliance with applicable WW RoHS materials restriction requirements.	Security features	network ports and protocols, SNMPv3, 8021x compatibility, TLS/SSL, Semi-permanent-queue Erase, NTLM v2, HP Web JetAdmin, HP
Shipping 62 x 24.8 x 30.7 in	Dimensions (WxDxH)	
Weight Printer 156.5 lb Shipping 213.8 lb Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified links, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW ROHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Printer	55.4 x 28.3 x 38.1 in
Printer 156.5 lb Shipping 213.8 lb Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICSS), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCC); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW ROHS materials restriction requirements.	Shipping	62 x 24.8 x 30.7 in
Shipping 213.8 lb Included	Weight	
Included What's in the box HP DesignJet XT950 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEER, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Printer	156.5 lb
What's in the box	Shipping	213.8 lb
printer stand, spindle, guide, warranty flyer, power cord HP Software and solutions HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (RSM), India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WERACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	Included	
Environmental ranges Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	What's in the box	
Operating temperature 41 to 104°F Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WB REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	HP Software and solutions	
Operating humidity 20 to 80% RH Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (RSM), India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Environmental ranges	
Operating altitude Up to 9843 ft Storage temperature -13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WRHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	Operating temperature	41 to 104°F
Storage temperature -:13 to 131°F Recycled plastic in printer 36% Acoustics Sound pressure -:	Operating humidity	20 to 80% RH
Recycled plastic in printer 36%	Operating altitude	Up to 9843 ft
Acoustics Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (idle) Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WB-RSACH, ErP). In compliance with applicable WW ROHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Storage temperature	-13 to 131°F
Sound pressure Printing: 42 dB(A) (operating), <16 dB(A) (fidle)	Recycled plastic in printer	36%
Sound power Printing: 5.8 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Acoustics	
Power Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 12 A max Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Sound pressure	Printing: 42 dB(A) (operating), <16 dB(A) (idle)
Consumption 35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (standby). Autoscheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	Sound power	Printing: 5.8 B(A) (operating), <3.4 B(A) (idle)
scheduled printer on/off usage. Requirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 Amax Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	Power	
Certification Safety USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentino (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	Consumption	
Safety	Requirements	Input voltage (auto ranging): 100-240 V (\pm 10%), 50/60 Hz (\pm 3 Hz), 1.2 A max
compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentino (IRAM); India (BIS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Certification	
Canada (ICES), EU (RED Directive), Australia (AČMA), New Zealand (RSM), China (CCC), Japan (VCC); Korea (KCC) Environmental ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty, Warranty and support options	Safety	compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina
(including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements. Warranty One-year limited hardware warranty. Warranty and support options	Electromagnetic	Canada (ICES), EU (RED Directive), Australia (AČMA), New Zealand
	Environmental	(including WEEE, RoHS, REACH, ErP). In compliance with applicable
	Warranty	One-year limited hardware warranty. Warranty and support options vary by product, country and local legal requirements.

Ordering information

· · · · · · · · · · · · · · · · · · ·	<i>,</i>	
Product		
2Y9H3F	HP DesignJet XT950 36-in Multifunction Printer	
Accessories		
7F2C8A	HP DesignJet 36-in Spindle	
CN538A	HP DesignJet 3-in Core Adapter	
Original HP printing supplies		
498N0A	HP 739 DesignJet Printhead Replacement Kit	
498Q0A	HP 738M 300-ml Black DesignJet Ink Cartridge	
676M9A	HP 738M 300-ml Cyan DesignJet Ink Cartridge	
676N0A	HP 738M 300-ml Magenta DesignJet Ink Cartridge	
676N1A	HP 738M 300-ml Yellow DesignJet Ink Cartridge	
A24VLA	HP 738M 130-ml Black DesignJet Ink Cartridge	
A24VMA	HP 738M 130-ml Cyan DesignJet Ink Cartridge	
A24VNA	HP 738M 130-ml Magenta DesignJet Ink Cartridge	
A24VPA	HP 738M 130-ml Yellow DesignJet Ink Cartridge	
Use Original HP i	nks and printheads, and HP large format printing materials, to experience	

consistent high quality and reliable performance that enable less downtime. These critical

components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks

Original HP large format printing materials

HP Universal Bond Paper (FSC* certified)⁶ (recyclable)⁷
HP Coated Paper (FSC* certified)⁶ (recyclable)⁷

HP Heavyweight Coated Paper (FSC* certified)⁶ (recyclable)⁷

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U56T9E HP 3-year Next Business Day HW Support U56TBE HP 4-year Next Business Day HW Support U56TCE HP 5-year Next Business Day HW Support

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

Specification Footnotes

- ¹Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.
- 2 ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll
- ³ With HP Universal Instant Dry Photo Gloss media with Original HP inks.
- ⁴ Scanned at 200 dpi using "Long Plot" setting.
 ⁵ Based on test results using 80 g/m² plain paper and standard configuration. Capacity is subject to paper type, printed file, and ambient conditions.
- ⁶ BMG trademark license code FSC*-C115319, see http://www.fsc.org . HP trademark license code FSC*-C017543, see http://www.fsc.org
- $^{7}\,\mathrm{Can}$ be recycled through commonly available recycling programs.

